

SHAFER ENTERPRISES, LLC

**COOL SHIRT®**

*Personal Cooling Systems*

10 Andrew Drive Suite 200

Stockbridge, GA 30281

Sales & Service 800-345-3176 Fax 678-289-4325

[www.coolshirt.net](http://www.coolshirt.net)



*Emergency Safety Pull Release Connectors* are patent-pending connectors designed for emergency situations where the user needs immediate release from the cooling unit.

The connectors release under pressure without requiring the user to locate and depress the normal release buttons. This is done by pulling on the shirt hose that connects the **COOL SHIRT** to the insulated hose. At 17 lbs of pressure, the fittings auto-release from the cooling unit hose.

To install your new connectors on the shirt and hose, follow these steps:

- 1) Remove your existing male connectors from your shirt by simply cutting them off from the clear tubing just behind the connectors.
- 2) Install the **red** male 5/16 inch barb connectors to the remaining tubing by stretching the tubing open slightly with a pair of needle nose pliers; dip the barbed end of the new **red** male connectors into some soapy water to lubricate them and insert the barbed ends into the clear tubing until fully seated against the connector.
- 3) Remove your existing female connectors from the end of your insulated hose (female connectors have the release push-buttons) by simultaneously cutting the insulation and internal black tubing just behind the connectors.
- 4) Install the **red** female 1/4 inch barb connectors to the black internal tubing by stretching the tubing open slightly with a pair of needle nose pliers, dip the barbed end of the new **red** female connectors into some soapy water to lubricate them and insert the barbed ends into the black tubing until fully seated against the connector.

Visit our website at

[www.COOLSHIRT.net](http://www.COOLSHIRT.net)