



**ELIMINATE
HEAT INDUCED
FATIGUE**

**The World Leader
in Personal Cooling**

COOL SHIRT® *Port-a-Cool ADAPTOR KIT*

The **PORT-A-COOL SHIRT** must be tested for leaks before it is worn each time by attaching the intake and exhaust black tubes to the shirt and depressing the dispenser nozzle for a couple of seconds. If coolant leaks are found while testing or wearing the shirt, discontinue use and return the shirt for repair or replacement. Avoid eye contact with gas. Do not restrict discharge tube.

INSTRUCTIONS: IMPORTANT: BEFORE CONNECTING FREEZE SPRAY CAN connect the black intake and exhaust tubing kit to the shirt. For best results connect the Porta-Cool can to spray into the back of the shirt. Test the shirt as above and then put on the shirt next to your skin with the tubing facing out. The shirt should fit snugly. Place the discharge tubing outside your clothing. Attach the can and hold upright. Depress the dispenser nozzle to release the coolant. Four to five one second bursts should be sufficient to initiate cooling. Dispense coolant as needed.

WARNING: The refrigerant gas can cause frost bite if sprayed directly on the skin.

WASHING INSTRUCTIONS: Disconnect the black discharge and supply tubing. The shirt may be washed in a washing machine and either hung to drip dry or dried in a dryer if placed in a laundry bag.

COOL SHIRT & Shafer Enterprises, LLC and distributors or retailers are not responsible for injury caused by misuse, user neglect, or malfunction.

All products are guaranteed for one year from the initial date of purchase for defects in material and workmanship. If you have any questions, please call Shafer Enterprises Customer Service at (800)345-3176. We appreciate your interest in our personal cooling products.

SE-012006